09/778,967

07650001aa

Reply to office action mailed 08/11/2004

The following is a complete listing of all claims in the application, with an indication of the status of each:

Listing of claims:

1	1. (currently amended) System for authenticating digital information,
2	comprising:
3	a) an image acquisition device for producing an original array of
4	two-dimensional digital information;
5	b) means for obtaining current date and time information from satellite
6	or radio broadcasts;
7	c) means for obtaining current location information from satellite or
8	radio broadcasts;
9	d) means for identifying a Sensor ID for the image acquisition device;
10	e) an encoder for converting date/time, location, and Sensor ID into
11	two-dimensional format called the Encoded Data Array;
12	f) an embedder for combining the Encoded Data Array and the
13	Original Array into a new Composite Array
14	g) an encrypter for transforming the Composite Array into another
15	two-dimensional array called the Encrypted Composite Array;
16	h) a Transmission Process device to transfer the Encrypted Composite
17	Array to the intended a recipient;
18	i) a decrypter to restore the Composite Array
19	n) means for comparing said transferred Composite Array to said
20	Encoded Data Array, said comparing means thereby being able to determine
21	whether said Encoded Data Array is embedded in said Composite Array;
22	j) a decoder with fault indicator when date/time, location, and source
23	cannot be decoded;

09/778,967 07650001aa Reply to office action mailed 08/11/2004

24	k) an Encoding Extractor for removing the Encoded Data Array from		
25	the Decrypted Composite Array;		
26	l) means for restoring the Original Array at pixel locations used for the		
27	Encoding; and		
28	m) means for determining changes between the Restored Original		
29	Array and the Original Array.		
1	2. (currently amended) System as in Claim 1 in which the Original Array		
2	size is increased by a factor and subpixels are used in steps f through, h, n, j,		
3	<u>k, l, and</u> m.		
1	3. (currently amended) System as in Claims 1 and 2 claim 20 in which the		
2	encryption of step g and decryption of step i is repeated more than one time.		
1	4. (currently amended) System as in Claims 1 and or 2 in which the		
2	encryption process involves scrambling the pixels or subpixels.		
1	5. (currently amended) System as in Claims 1 and or 2 in which steps b and or		
2	utilize the GPS (Global Positioning Satellite) system.		
1	6. (currently amended) System as in Claims 1 and or 2 in which the Decoder		
2	utilizes FlashCorrelation« flash correlation to select pixel locations of the		
3	Encoded Data Array and test for authenticity.		
1	7. (currently amended) System as in Claims 1 and or 2 in which the Sensor		
2	ID in step d includes a biometric identifier of the User of the image		
3	acquisition device.		
,	and another and the control of the c		

09/778,967

MIKOS-101

3

another device.

07650001aa

Reply to office action mailed 08/11/2004 Amendment dated 02/11/2005 8. (currently amended) System as in Claims 1 and or 2 in which the Sensor 1 2 ID in step d includes the serial number and odometer setting of the image 3 acquisition device of step a. 1 9. (currently amended) System as in Claims 1 and or 2 in which the change 2 detector of step m evaluates subsections of the Restored Original Array and the Original Array to localize areas of difference. 3 1 10. (currently amended) System as in Claim 6 in which FlashCorrelationα 2 <u>flash correlation</u> is used to verify that the encoded data is the same as data 3 which is expected to be encoded into a particular Original Array. 11. (currently amended) System as in Claim 6 in which FlashCorrelation 1 2 flash correlation is used to identify the encoded data by exhaustive 3 comparison against each possible value for each of date/time, location, and 4 source. 1 12. (currently amended) System as in Claims 1 and or 2 in which date/time, 2 location, and source are annotated onto the Encrypted Composite Array. 13. (currently amended) System as in Claims 1 and or 2 in which the 1 2 encoded data provides the key to the encryption and decryption algorithms. 14. (currently amended) System of Claims 1 and or 2 in which the operation 1 2 of the EIS image acquisition device is triggered by the change of status of

	MIKOS-101	09/778,967	07650001aa
	Amendment dated 02/11/2005	5 Reply to office a	ction mailed 08/11/2004
1	15. (original) System	n of Claim 14 in which the trigge	ering device is a face
2	recognition system.		
1	16. (original) System	n of Claim 14 in which the trigge	ering device is a speed
2	sensor.		
1	17. (original) System	of Claim 14 in which the trigge	ering device is an alarm
2	, , ,		· ·
1	18. (currently amende	ed) System of Claims 1 and or 2	in which the Encoding
2	is performed by overla	is performed by overlaying a pattern of pixels of a particular color or grey	
3	•		
1	19. (currently amende	ed) System of Claims 1 and or 2	in which the Encoding
2			-
1	20. (currently amende	ed) System of Claims 1 and or 2	in which no encryption
2	or scrambling is perfo	rmed, further comprising:	
3	g) an encrypte	r for encrypting the Composite A	Array;
4	i) a decrypter t	to restore the Composite Array.	
1	21. (original) A meth	nod for authenticating digital ima	ages, comprising the
2	steps of:		
3	capturing a dig	gital image;	
4	recording auth	entication information at the tim	e and place of said

capturing, said authentication information being unique to said digital image

and including at least one piece of information from a source independent of

5

6

7

said capturing;

09/778,967

967 07650001aa Reply to office action mailed 08/11/2004

8 encoding said authentication information into a data array mapable to 9 said digital image; 10 mapping said data array to said digital image, thereby creating a 11 composite array; 12 optionally encrypting said composite array; optionally annotating said composite array; 13 14 comparing said data array, optionally encrypted and annotated, to a target composite array, wherein said comparing determines whether said 15 authentication information is embedded in said target composite array, 16 17 thereby proving that said target composite array is an authentic copy of said 18 composite array. 22. (original) The method of claim 21, wherein said at least one piece of 1 2 information from a source independent of said capturing is GMT time 3 information. 1 23. (original) The method of claim 21, wherein said at least one piece of information from a source independent of said capturing is GPS location 2 3 information. 1 24. (original) The method of claim 21, wherein said at least one piece of information from a source independent of said capturing is GMT time 2 3 information and GPS location information. 25. (currently amended) The method of claim 21, wherein said comparing 1 2 step is flashcorrelation flash correlation of said data array with said target 3 composite array.

09/778,967

07650001aa

Reply to office action mailed 08/11/2004

1	26. (currently amended) The method of claim 25, wherein said digital image		
2	is a sequence of digital images, there being a unique set of authenticating		
3	information for each digital image in said sequence and a corresponding		
4	unique data array, there being a unique composite array corresponding to each		
5	digital image in said sequence, wherein said composite array is a sequence of		
6	composite arrays and said target composite array is a sequence of target		
7	composite arrays, and wherein said flashcorrelation flash correlation		
8	determines whether said sequence of target composite arrays is an authentic		
9	copy of said sequence of composite arrays.		
1	27. (currently amended) The method of claim 26, wherein said sequence of		
2	digital images is a video image and said flashcorrelation flash correlation is		
3	done in real time.		
1	28. (original) A system for authenticating digital images, comprising:		
2	means for capturing a digital image;		
3	means for recording authentication information at the time and place		
4	of said capturing, said authentication information being unique to said digital		
5	image and including at least one piece of information from a source		
6	independent of said capturing;		
7	means for encoding said authentication information into a data array		
8	mapable to said digital image;		
9	means for mapping said data array to said digital image, thereby		
10	creating a composite array;		
11	means for optionally encrypting said composite array;		
12	means for optionally annotating said composite array;		
13	means for comparing said data array, optionally encrypted and		
14	annotated, to a target composite array, wherein said comparing determines		

MIKOS-101 09/778,967 07650001aa
Amendment dated 02/11/2005 Reply to office action mailed 08/11/2004

15	whether said authentication information is embedded in said target composite
16	array, thereby proving that said target composite array is an authentic copy of
17	said composite array.
1	29. (original) The system of claim 28, wherein said at least one piece of
2	information from a source independent of said capturing is GMT time
3	information.
1	30. (original) The system of claim 28, wherein said at least one piece of
2	information from a source independent of said capturing is GPS location
3	information.
1	31. (original) The system of claim 28, wherein said at least one piece of
2	information from a source independent of said capturing is GMT time
3	information and GPS location information.
1	22 (1
1	32. (currently amended) The system of claim 28, wherein said comparing
2	step is flashcorrelation flash correlation of said data array with said target
3	composite array.
1	33. (currently amended) The system of claim 32, wherein said digital image
2	is a sequence of digital images, there being a unique set of authenticating
3	information for each digital image in said sequence and a corresponding
4	unique data array, there being a unique composite array corresponding to each
5	digital image in said sequence, wherein said composite array is a sequence of
6	composite arrays and said target composite array is a sequence of target
7	composite arrays, and wherein said flashcorrelation flash correlation

MIKOS-101 09/778,967 07650001aa Amendment dated 02/11/2005 Reply to office action mailed 08/11/2004

- determines whether said sequence of target composite arrays is an authentic copy of said sequence of composite arrays.
- 1 34. (currently amended) The system of claim 33, wherein said sequence of
- digital images is a video image and said flashcorrelation flash correlation is
- 3 done in real time.